Digital Video Recorders Quick Guide



BOSCH

Invented for life

















			manufacture and			A STATE OF THE PARTY OF THE PAR		000	
	Bosch Digita	al Video Recorders	DVR1A	DVR1C	DVR4C	Divar	Divar MR	DiBos Micro	DiBos Rackmount
	Operating System		Embedded	Embedded	Embedded	Embedded	Embedded	Windows XP Embedded	Windows XP Embedded
Ē	Rack Mountab	ole	No	No	No	Yes	Yes	Yes	Yes
Sys	SDK Available		No	No	No	Yes	No	HTML Interface	HTML Interface
	Warranty		3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years
	Input	Channels	1	1	4	6, 9, 16	8, 16	Analog: 6, 12 IP: 8	Analog: 6, 12, 18, 24, 30 IP: 16, 32
<u>8</u>	Output	Looping Video	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Video		Composite Outs	1	1	1	2	2	2	2
		VGA	No	No	No	No	1	1	1 (plus optional 2nd)
		Spot Monitor	No	No	No	Yes	1	2	2
	Input	Channels	0	2	4	n/a	4, 8	2, 4 (plus 8 from IP)	2, 4, 6, 8, 10 (plus up to 32 from IP cameras)
	Output	Channels	0	2	4	n/a	1	1	1
ğ	Compression 7	Туре	n/a	ADPCM	ADPCM	n/a	ADPCM2	G.726	G.726
₹	Sample Rate		n/a	8 KHz	8 KHz	n/a	8 KHz	32 KHz	32 KHz
	Synchronous A	Audio	n/a	Yes	No	n/a	Yes	No	No
	Associate Mult	tiple Cameras to 1 Audio	n/a	n/a	No	n/a	Yes	Yes	Yes
	Inputs		1	1	4	6, 9 or 16 (one per video channel)	8, 16	12	32
	Relay Outputs		1	1	4	4	4, 8	12	16
	Call Up Pre-po	osition on Dome Cameras	n/a	n/a	n/a	Yes	No	Yes	Yes
	Increase Fram	e Rate on Alarm	Yes	Yes	Yes	Yes	Yes	Yes	Yes
S	Simultaneous	normal and event recording	Yes	Yes	Yes	Yes	No	Yes	Yes
arn	Multiple Came	era Linking on Alarm Event	n/a	n/a	Yes	No	No	Yes	Yes
Ala	Notification via	a e-mail	No	No	Yes	No	Yes	Yes	Yes
	Notification to	Remote PC	No	No	Yes	Yes	Yes	Yes	Yes
	Pre-alarm		Up to 220 Seconds	Up to 220 Seconds	Up to 30 Seconds	30 Seconds	Up to 60 Seconds	Yes	Yes
	Alarm Time		Unlimited	Unlimited	Up to 120 Seconds	Up to 60 Seconds	Up to 10 Minutes	Yes	Yes
	Motion Detect	tion	No	No	Yes	Yes	Yes	Yes	Yes
	Compression	Video	M-JPEG	M-JPEG	MPEG-4	Wavelet	MPEG-4	MPEG-4, JPEG	MPEG-4, JPEG
	Compression	Software or Hardware	Hardware	Hardware	Hardware	Hardware	Hardware	Video Hardware	e, Audio Software
	Frame Rate	PAL	50 IPS @ CIF	50 IPS @ CIF	100 IPS @ CIF	50 IPS @ 2CIF	400 IPS @ CIF	75/150 @ CIF	75/150/225/300/375 @ CIF
	(IPS)	NTSC	60 IPS @ CIF	60 IPS @ CIF	120 IPS @ CIF	60 IPS @ 2CIF	480 IPS @ CIF	90/180 @ CIF	90/180/270/360/450 @ CIF
	IPS per Camera	PAL	25 IPS @ CIF (Normal) 50 IPS @ CIF (Alarm)	25 IPS (Normal) 50 IPS (Alarm)	25 IPS @ CIF	6 Ch.: 8.3 IPS @ 2CIF 9 Ch.: 5.0 IPS @ 2CIF 16 Ch.: 3.1 IPS @ 2CIF	25 IPS @ CIF	25 Per Camera Max 150 on a 12 Channel Unit @ CIF	25 Per Camera Max 375 on a 30 Channel Unit @ CIF
		NTSC	30 IPS @ CIF (Normal) 60 IPS @ CIF (Alarm)	30 IPS @ CIF (Normal) 60 IPS @ CIF (Alarm)	30 IPS @ CIF	6 Ch.: 10 IPS @ 2CIF 9 Ch.: 6.5 IPS @ 2CIF 16 Ch.: 3.75 IPS @ 2CIF	30 IPS @ CIF	30 Per Camera Max 180 on a 12 Channel Unit @ CIF	30 Per Camera Max 450 on a 30 Channel Unit @ CIF
	Recorded Video Resolution Individual Cam	PAL	352 x 288	352 x 288	352 x 288	720 x 288	352 x 288/704 x 288/704 x 576	CIF/2CIF/4CIF An	alog and IP Cameras
rding		NTSC	352 x 240	352 x 240	352 x 240	720 x 240	352 x 240/704 x 240/704 x 480	CIF/2CIF/4CIF An	alog and IP Cameras
ĕ		nera Adjustment (IPS, Quality)	n/a	n/a	No	Yes	Yes	Yes	Yes
_	Schedule Recording Modes		Daily/Weekday/Weekend/Specific Day		Day/Night/Weekend	Day/Night/Weekend/Specific Day	Day/Week/Specific Day	Day/Night/Weekend	/Holiday/Specific Day
	HDD Overwrite Warning		No	No	Yes	No	Yes	Yes	Yes
	Recording Times	Best Quality/Highest Res., 3 IPS Continuous, 50% Motion, Very Busy Scene (Outdoor), No Audio	6 Days (80 GB) @ CIF	12 Days (160 GB) @ CIF	7 Days (80 GB) @ CIF 13 Days (160 GB) @ CIF 26 Days (320 GB) @ CIF 50 Days (600 GB) @ CIF	6 Ch.: 5 Days (320 GB) @ 2CIF 9 Ch.: 4 Days (320 GB) @ 2CIF 9 Ch.: 7 Days (600 GB) @ 2CIF 16 Ch.: 4 Days (600 GB) @ 2CIF 16 Ch.: 6 Days (1000 GB) @ 2CIF	8 Ch.: 9 Days (500 GB) @ 4CIF 8 Ch.: 18 Days (1000 GB) @ 4CIF 16 Ch.: 9 Days (1000 GB) @ 4CIF 16 Ch.: 18 Days (2000 GB) @ 4CIF	6 Ch.: 10 Days (400 GB) @ 4CIF 12 Ch.: 5 Days (400 GB) @ 4CIF	6 Ch.: 19 Days (750 GB) @ 4CIF 12 Ch.: 10 Days (750 GB) @ 4CIF 18 Ch.: 9 Days (1000 GB) @ 4CIF 24 Ch.: 10 Days (1600 GB) @ 4CIF 30 Ch.: 8 Days (1600 GB) @ 4CIF
		Normal Quality/Standard Res., 3 IPS Continuous, 50% Motion, Very Busy Scene (Outdoor), No Audio	8 Days (160 GB) @ CIF	16 Days (160 GB) @ CIF	20 Days (80 GB) @ CIF 39 Days (160 GB) @ CIF 78 Days (320 GB) @ CIF 146 Days (600 GB) @ CIF	6 Ch.: 14 Days (320 GB) @ 2CIF 9 Ch.: 9 Days (320 GB) @ 2CIF 9 Ch.: 17 Days (600 GB) @ 2CIF 16 Ch.: 10 Days (600 GB) @ 2CIF 16 Ch.: 16 Days (1000 GB) @ 2CIF	8 Ch.: 36 Days (500 GB) @ CIF 8 Ch.: 72 Days (1000 GB) @ CIF 16 Ch.: 36 Days (1000 GB) @ CIF 16 Ch.: 72 Days (2000 GB) @ CIF	6 Ch.: 45 Days (400 GB) @ CIF 12 Ch.: 22 Days (400 GB) @ CIF	6 Ch.: 86 Days (750 GB) @ CIF 12 Ch.: 43 Days (750 GB) @ CIF 18 Ch.: 38 Days (1000 GB) @ CIF 24 Ch.: 46 Days (1600 GB) @ CIF 30 Ch.: 37 Days (1600 GB) @ CIF

Digital Video Recorders Quick Guide



BOSCH

Invented for life



	Bosch Dig	ital Video Recorders	DVR1A	DVR1C	DVR4C	Divar	Divar MR	DiBos Micro	DiBos Rackmount
	Internal HDD		80 GB	160 GB	80 - 160 - 320 - 600 GB	80 - 160 - 320 - 600 - 1000 GB	160 - 320 - 500 - 1000 - 2000 GB	250 - 400 GB	250 - 500 - 750 - 1000 - 1600 GB
o o		Supported Devices	Compact Flash	Compact Flash	USB 1.1	Internal CD/DVD Writer Remote Client	Internal CD/DVD Writer, USB 2.0	CD-RW, DVD, USB 2.0, Network Drive, SCSI	CD-RW, DVD, USB 2.0, Network Drive, SCSI
Storage	Export	Data Format	JPEG	JPEG	Native, AVI, or JPEG	Native File Format	Native File Format	Bosch, ASF	Bosch, ASF
ž		Back-up Mode	Manual	Manual	Manual	Manual	Manual or Automatic	Manual or Automatic	Manual or Automatic
	Support SCS	SI Disk Array	No	No	No	Yes, DVSA (Lite and Premium)	No	Yes, DVSA (Lite and Premium)	Yes, DVSA (Lite and Premium)
	Max. SCSI A	rray Configuration	n/a	n/a	n/a	12 TB*	n/a	13.8 TB**	13.8 TB**
	Timeline Sea	arch Bar (Color Coded)	No	No	Yes on Remote Software	Yes on Remote Software	Yes	Yes	Yes
Search	Search Mode	e	Date/time, Events	, or Recordings List	Date/time, Events, Motion, Text	Date/time, Camera Number, Events, Motion, Smart Motion Search	Date/time, Camera Number, Events, Motion, Bookmark, Smart Motion Search	Date/time, Camera Name, Events, Pr	e-Alarm, Motion, Smart Motion Search
	Smart Motion	n Search – Motion in specific area	No	No	No	Yes	Yes	Yes	Yes
	Live	PAL	720 x 576	720 x 576	720 x 576	720 x 576	720 x 576	CIF/2CIF/4CIF And	alog and IP Cameras
	Resolution	NTSC	720 x 484	720 x 484	720 x 484	720 x 484	720 x 484	CIF/2CIF/4CIF And	alog and IP Cameras
Display	Screen Divis	sion (Multi-screen)	Full, 2x2, 3x3 (w/ Q	uad or Mux attached)	Full, 2x2, Sequence	Full, 2x2, 3x3, 4x4	Full, Sequence, 2x2, 3x3, 4x4, 5+1, 7+1	Full, 2x2, 3x3, 4x4, 5x6	Full, 2x2, 3x3, 4x4, 5x6
	Digital Zoom	1	No	No	No	Yes	No	Yes	Yes
	Camera Lock	k-outs by User	No	No	No	Yes	Yes	Yes	Yes
		User Levels	1	3	2	6	3	Unlimited	Unlimited
Security/User Management		Add/Delete	No	No	No	Yes	Yes	Yes	Yes
₹ ₩	User Control	Set Viewing Permissions	No	No	Yes	Yes	Yes	Yes	Yes
urit nag		Centralized User Management	n/a	No	No	No	No	Yes - LDAP	Yes - LDAP
Sec		Event Logging by User	No	No	No	No	No	Yes	Yes
	Data Integrit	y Check (Watermarking, etc.)	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	Network	Connection	10BaseT Ethernet	10BaseT Ethernet	10/100 Ethernet	10/100 Ethernet	10/100 Ethernet	10/100/1000 Ethernet	10/100/1000 Ethernet
	INCLWOLK	Protocol	TCP/IP	TCP/IP	TCP/IP	TCP/IP	TCP/IP	TCP/IP, UDP Tunneling	TCP/IP, UDP Tunneling
S	Web Browse	er Access	No	Yes	No	Yes	Yes	Yes	Yes
SS	Simultaneou	s Accessible Users	n/a	4	5	6	5	20 with software;	5 with web browser
note Access		Resolution	n/a	n/a	720 x 576 (PAL) 720 x 484 (NTSC)	720 x 576 (PAL) 720 x 484 (NTSC)	352 x 288 (PAL) 352 x 240 (NTSC)	CIF/2CIF/4CIF And	alog and IP Cameras
쿒	Remote PC	Full Admin Control	n/a	n/a	Yes	Yes	Yes	Yes, Remote Desktop	Yes, Remote Desktop
	Client	PTZ Control	n/a	n/a	n/a	Yes	Yes	Yes	Yes
		Export Options	n/a	n/a	Native, AVI, or JPEG	Native File Format (all cameras), .AVI (single camera)	n/a		l Cameras) nd Multiple Camers)
.	Instant Playback		No	No	No	Yes	Yes	Yes	Yes
ä	Bilinx/Up-the-Coax Camera Control		No	No	No	Yes	No	Yes	Yes
eat	Digital Zoom on Playback		No	No	No	Yes	No	Yes	Yes
Other Features	PTZ Joystick Control ATM/POS Interface OPC Support		No	No	No	Yes	Yes	Yes - DiBos/Bosch VMS	Yes - DiBos/Bosch VMS
횽			No	No	No	Yes	No	No	No
			No	No	No	Yes	No	Yes	Yes
Ordering Information	Part Number	rs/Ordering Charts	DVR1A1081	DVR1C1161	DVR4C1081 (80 GB) DVR4C1161 (160 GB) DVR4C2161 (320 GB) DVR4C2301 (600 GB)	Inputs	DVR-8K-016A (160 GB) DVR-16K-032A (320 GB) DVR-8L-016A (160 GB/DVD) DVR-8L-032A (320 GB/DVD) DVR-8L-050A (500 GB/DVD) DVR-8L-100A (1000 GB/DVD) DVR-16L-032A (320 GB/DVD) DVR-16L-050A (500 GB/DVD) DVR-16L-050A (500 GB/DVD) DVR-16L-000A (2000 GB/DVD) DVR-16L-00A (2000 GB/DVD)	Type 06 040 040 040 040 040 040 040 040 040	Inputs Capacity (s. 10 GB) Capacity (s. 10 GB) Capacity (s. 10 GB) Capacit

Due to SCSI specifications, the daisy chaining of more than two Digital Video Storage Array subsystems (DVA-08K/DVA-16K) on a single Divar is NOT RECOMMENDED. Divar can address up to 6 SCSI IDs (7 for units without DVD writer) and a maximum of 2TB per ID (12TB with DVD writer or 14TB for units without a DVD writer) Stated capacities assume JBOD configuration 8% overhead on the HDDs.

Due to SCSI specifications, the daisy chaining of more than three Digital Video Storage Array subsystems (DVA-08K/DVA-16K) on a single DiBos is NOT RECOMMENDED. The maximum configuration is (2) DVA-16Ks or (1) DVA16K and (2) DVA08Ks daisy chained. Stated capacities assume JBOD configuration and 8% overhead on the HDDs.